

# SYNTELAN LSP 03

Lepilo za posebne namene



**Syntelan LSP 03** je dvokomponentno lepilo na bazi sintetičkog kaučuka rastvorenog u organskim rastvaračima. Otporno je na vodu i ulje.

## Tehničke karakteristike

Boja:	bela
Viskozitet: (FØ6)	220-240 s
Gustina:	0,85 g /cm <sup>3</sup>
Suva masa:	min 21 %
Rok upotrebe:	12 meseci
Potrošnja:	≈ 200g/m <sup>2</sup>

## Namena

Lepilo **Syntelan LSP 03** se koristi za lepljenje unutrašnje i spoljašnje gume sa armaturom u proizvodnji gumenih creva za ulja, naftu i naftne derivate, komprimovani vazduh, vodu i neagresivne tečnosti, rashladne tečnosti, peskarenje, kočione uređaje.

## Uputstvo za upotrebu

Površine koje se lepe moraju biti suve i čiste

Pre upotrebe lepilu dodati oko 10 % Utvrđivača R i dobro promešati (tako pripremljeno lepilo upotrebljivo je oko 2 časa).

Pripremljeno lepilo se nanosi automatski na impregniranu podlogu, na koju se posle kraćeg vremena sušenja navlači gumeno crevo, nakon čega se površine slepljuju i pod pritiskom presuju.

## Napomena

Uputstvo o načinu upotrebe prilagoditi lokalnim uslovima rada i materijalima koji se lepe.

## Pakovanje

Lepilo se isporučuje u ambalaži od 1, 4, 20 litara.

## Skladištenje

U dobro zatvorenoj ambalaži, na suvom mestu na temperaturi od + 5° C do + 25° C (278K -298K)



# SYNTELAN LSP 03

Adhesive for special purposes



**Syntelan LSP 03** is a two component adhesive based on synthetic rubber dissolved in organic solvents. It water and oil resistant.

## Technical characteristics

Colour:	White
Viscosity (FØ6)	220-240 s
Density:	0.85 g/cm <sup>3</sup>
Dry matter:	min 21%
Consumption:	≈ 200g/m <sup>2</sup>

## Application

Adhesive **Syntelan LSP 03** is used for bonding inside and outside rubber with armature in production of rubber hoses for oil, petrol, petrol derivates, compressed air, water, non aggressive fluids, coolants, sandblasting and brake systems.

## Instruction for use

Surfaces must be dry and clean.

Before using, add about 10% of Hardener R and mix the adhesive well before using. (Prepared like this, it is about usable about two hours).

Apply the adhesive automatically, on impregnated surface, and after short time pull over rubber hose and bond the surfaces with pressure.

## Note

Instruction for use should be adjusted to local working conditions and materials that are used.

## Packing

Adhesive Syntelan LSP 03 is available in packaging of 1; 4 and 20 liters.

## Storage

Keep in well sealed packaging at the temperature between +5°C to +25°C (278K do 298K).

