

# GUMIRANA PLUTA



**Gumirana pluta** je izrađena od određenog granulata plute i kaučuka otpornog na ulje i temperaturu do 125°C (398 K).

## Tehničke karakteristike

	Jedinica mere	Vrednost
Tvrdoća	Sh	75 ± 5
Specifična težina	g/cm <sup>3</sup>	0,9 – 1
Faktor savitljiv.		12
Jačina na kidanje	N/mm <sup>2</sup>	min2,10

## Namena

Gumirana pluta je namenjena za izradu dihtunga (zaptivki) koji se koriste za zaptivanje kod motora sa unutrašnjim sagorevanjem, transformatora, uljnih agregata plinskih uređaja, uređaja za transport nafte, naftnih derivata itd.

## Način isporuke

Gumirana pluta se isporučuje u tablama veličine 1200 x 900 mm i debljine 1,50 do 12,00 mm.

## Skladištenje

Gumirana pluta se skladišti u prostorijama zaštićenim od uticaja vlažnosti i sunčeve svetlosti na temperaturi oko 15°C.



# RUBBER CORK



**Rubber Cork** is manufactured from high-quality granulated cork and rubber. It is oil and temperature resistant (up to 125°C or 398 K).

## Technical characteristics

	Unit	Value
Hardness	Shore	75 ± 5
Specific weight	g/cm <sup>3</sup>	0,9 – 1
Flexibility factor		12
Tensile strength	N/mm <sup>2</sup>	min2,10

## Application

Rubber Cork is used in making gaskets (sealants) at internal combustion engines, transformers, oil aggregates of gas appliances, machines for petroleum transport, petroleum derivatives, etc.

## Delivery form

Rubber Cork is delivered in sheets, dimensions: 1200 x 900 mm and thickness: 1,50 do 12,00 mm.

## Storage

Rubber Cork should be stored protected from moisture and sunlight and in temperature of approximately 15°C.

