

SINTEX 33

Trajno plastična zaptivna masa



Sintex 33 se koristi u auto industriji, građevinarstvu, brodogradnji i industriji bele tehnike za zaptivanje pukotina i sastava (na zavarenim i nezavarenim spojevima). Ima veliku moć prijanjanja na obrađene i neobrađene limove.

Tehničke karakteristike

Sintex 33 je trajno plastična, vodootporna, nezapaljiva zaptivna masa. Izrađuje se u vidu profila prečnika 10 mm (ili u drugim dimenzijama po želji kupca), izvučenih na rolo papiru. Postojan je na temperaturi od -40 do +170°C i otporan na vremenske uticaje. Rok upotrebe neograničen.

Uputstvo za upotrebu

Sintex 33 se nanosi ručno na površine koje su suve, odmašćene i očišćene od prašine. Da bi se postigao odgovarajući efekat prijanjanja dovoljan je pritisak ruke. Masa se lako oblikuje po želji. Ruke se lako čiste krpom natopljenom u benzinu.

Pakovanje

Isporučuje se u pakovanju od 0.200kg i 1kg.

Skladištenje

Skladišti se u prostorijama sa normalnim uslovima pri čemu treba voditi računa da se masa ne deformiše prilikom slaganja i na istu ne lagerovati drugu robu.

Napomena

Ne podleže SRPS-u



SINTEX 33

Permanent Plastic Sealant



Sintex 33 is used in automotive industry, construction industry, shipbuilding industry, home appliances industry, for sealing cracks and bonds (on welded and unwelded rabbets) It has a great ability to bond on processed and unprocessed sheet metals.

Technical characteristics

Sintex 33 is permanently plastic, water resistant, inflammable sealant. It is made in form of rolls, in diameter of 10 mm (or other dimensions according to our customer special demand), sorted on roll paper.

It is stable on temperatures from -40 to +170°C and resistant to different weather conditions.

Expiration date is unlimited.

Instruction for use:

Apply Sintex 33 manually on dry, degreased and clean surfaces. To get proper effect of adhesion, it is recommended to press with hands and fingers. You can easily shape the mass according to your needs. Hands can be easily cleaned with cloth deepened into benzene.

Packaging

The sealant is delivered in packaging from 0.200 kg and 1kg.

Storage

Store in premises in normal conditions, pay attention not to deform mass while stacking, and do not put other goods on it.

Note

It does not apply to SRPS

